

## MITCHELL COUNTY CREP WETLAND PROJECT

SITE Mit981810C MITCHELL COUNTY, IOWA







SECTION 10, T-98-N, R-18-W MITCHELL COUNTY, IOWA

#### PREPARED FOR:

IOWA DEPARTMENT OF AGRICULTURE AND LAND STEWARDSHIP HENRY A. WALLACE BUILDING DES MOINES, IOWA 50319

#### HORIZONTAL CONTROL

SEE INDIVIDUAL SHEETS


#### VERTICAL CONTROL

THE ELEVATIONS ON THIS PLAN ARE BASED ON THE NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD).

#### **CIVIL ENGINEERS / SURVEYORS**

SEH Yaggy 215 NORTH ADAMS MASON CITY, IOWA 50401 PHONE NO. (641) 424-6344 FAX NO. (641) 424-0351

MITCHELL COUNTY



#### SHEET INDEX

C.01	TITLE SHEET
C.02	GENERAL INFORMATION SE
C.03	SITE PLAN
C.04	STRUCTURE PLAN
C.05	SHEET PILE STRUCTURE
C.06	DETAILS
C.07	DETAILS

PRINTED

DEC 2 9 2014

SEH - Mason City, IA

#### OFFICIAL COPY

#### **BENCH MARKS**

1. CONTROL PT. 601	EL. 1236.51
2. CONTROL PT. 602	EL. 1202.72
3. CONTROL PT. 608	EL. 1177.18
4. CONTROL PT. 609	EL. 1192.47



MITCHELL

PROJECT
NUMBER 12114
COMPUTER
FILE 12114C01.DWG

DATE 05/15/1014

DRAWN BY AH

CHECKED BY RGL

#1 12-22-14

C.01

I hereby certify that this engineering document was prepared by me or under my direct personal supervisions and that I am a duly licensed Profession and the I am a duly licensed Profession and I am a duly license and I

SEH YAGGY PHONE: (641) 424-6344 215 N. ADAMS AVE. MASON CITY, IA 50401

TITLE SHEET

7 SHEE

#### STANDARD ABBREVIATIONS

SIAN	IDARD ABBREVIAL	ION2			
A 2 0 0 AC.C. A.D. ADD. ADD. ADD. AGG. ALT. AP.P.S. AP.P.S. AP.P.S. AP.P.S. AP.R.S. AP	ANGLE CENTRAL ANGLE ACRES ASPAULTO CEMENT CONCRETE AREA DRAN ADDENDUM ADDENDUM ADDENDUM ALTERNATE/ALTERATION ACCESS PANEL ALTERNATE PRESSURE PIPE SEWER ALTERNATE PIPE SEWER ALTERNATE PIPE SEWER APPROXIMATE ASPAULT	F FDN. FE. ST. ST. ST. ST. ST. ST. ST. ST. ST. ST	FOUNDATION FIELD ENTRANCE FINSH FINSH FLOOR FORESIGHT FOOT OR FEET FOOTING FURNISH FUTURE  GAS GENERAL CONTRACTOR GUITERLINE GROUND GRAVEL GATE VALVE	R R. C.B. R. C.P. REC.FT. REC.FT. REG. REON. REO. REO. R. R. C. R. R. C. R. R. C. R.	RADIUS/RANGE RENFORCED CONCRETE BOX (CULVERT RENFORCED CONCRETE PIPE ROOF ORAN ROAD RENFORCING BAR RECEPTIOLE RECEPTION RECTANGULAR REFERENCE. REGULATION REINFORCED RETURN/RETAINING REVISON ROOM ROOF WAY ROHE ROOF WAY ROUGH REMONE AND REPLACE REMOYE AND SALVAGE REMOYE AND SALVAGE REGUE REMOYE AND SALVAGE
B B-B B/C B/L BLDG. BLVD. B.M. B.O. BOT. BRG. B.S. BSMT. BTWN. B.V.	BACK OF CURB TO BACK OF CURB BACK OF CURB BITUMNOUS BASE LINE BUTUMNOUS BUSE LINE BUTUMNOUS BENCH HARK BY OTHERS BOTTOM BEARING BLACK SIGHT BUSEMENT BUTUMENT BUTUMENT BUTUMENT BUTUMENT BUTUMENT BUTUMENT BUTUMENT BUTUMENT	H HCP. HDR. HJ. HORIZ. H.PT. HR. HT. HWY. HWO.  1.0. I LE. IMP. INFO.	HANDICUP HEADER HEADER HEIGHT INSTRUMENT HORZONTAL HIGH POINT HOUR HEIGHT HIGHWAY HORNET INSIDE DUMETER/INSIDE DIMENSION INVERT ELEVATION INVERT ELEVATION INCHES INCHES INFORMATION	R.AR. R.AS. RT. S.S. S.A. SC. S'LY SAN. SAN.S.S.B. SCHD. S.D.R. SEC. SECT. SECT.	SOUTH SANTIARY SEWER ALIGNMENT SEALCOAT SOUTHERLY SANTIARY SANTIARY SOLE BORING SCHEDULE STANDARD THERMOPLASTIC PIPE DMENSON RATIO
C C-C CAGC CAGC CAGC CAGC CAGC CAGC CAGC C	CORRUGATED METAL PIPE CLEAN OUT COUNTY COUNTY COMPOSTE/COMPOSITION CONFEROUS ONCRETE ONORRET CONNECTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTS CORPORATE COLOR OS TREATMENT CORPORATE COLOR OS TREATMENT CORPORATE COLOR OS TREATMENT	INL. INSP. INSP. INST. INT. I.P. J.B. J.C. L.C. L.C. L.C. L.C. L.C. L.C. L.C	INLET INSPECTION INSPALIATION INSPALIATION INSTALLATION INSTALLATION INSPALIATION INTAKE INVERT IRON PIPE JUNCTION BOX JOINT LOUND LONGTH POUND LATERAL_CONNECTION LANDSOLPE LINEAL_FOOT LAMP HOLE LINES LIVE LOAD LAND LOW POINT LOHE LOW POINT LOHE MANTENANCE/MAINTAIN MATERIAL MAXIMUM MATERIAL MAXIMUM MEANDER CORNER MECHANICAL MEMBRANCE MINISPACTURER MANTENCE MINISPACTURER MANTENCE MINISPACTURER MANTENCE MEMBRANCE MINISPACTURER MANTENCE	SERV. SERV. SHIT. SUR. SUR. SUR. ST. A. STD. STRUCT. SUR. SUR. SUR. SUR. SUR. SUR. SUR. SUR	SECTION SECTION SOUTHEASTERLY SERVICE SOURCE FEET SHEET SHEET SHEAT SEALEN SEALEN SEALEN SEALEN STORES STREET STREET STREET STREET STROME STORMES STREET STORMES STREET STORMES STRUE STORMES STRUE STORMES STRUE STORMES STRUE STORMES STRUE STORMES STRUE STRUE STORMES STRUE STORMES STRUE ST
CULV. C.W. C.Y.  D BL DECO DEPT. DET. DIA DIM. D.I.P. DISP. D.L DN. D.O. DR. D.S.P. DWG.	CULVERT COLD WATER CUBIC YARD  DOUBLE  BRAINAGE EASEMENT  BEPARTUENT DETAIL DUMETER DUGONUL DIMETER DUCTILE IRON PIPE DISPOSAL DEAD IOAD  DOWN	MISC. MOD. MON. N. N. N. N'LY. NELY. NULY. NULY. NO. NO. N.T.S. O O.C. O.D. OFF.	MISCELLANGOUS MODEY/AUQUILE MONUMENT MORTH NOT APPLICABLE, NOT AVAILABLE NORTHERY NORTHANT NORTHANT NORTHANTSTERLY NOT IN CONTRACT NUMBER NOMAL NOT TO SCALE OFFERALL ON CENTER OUTSIDE DUMETER OVERHEAD ELECTRIC OVERHEAD BLECTRIC	TH. THK. TO.C. TO.B. TO.P. TO.P. TO.P. TO.P. T.P. T.Y. T.Y. T.Y. U.B.C. U.E. UE UG U.L. U.N.O. UP	THICK TOP OF CONCRETE TOP OF BEAM TOP OF DEAM TOP OF DECK TOP OF FOOTING TOP OF PAYENET TOP OF WALL TURNING POM TOE OF SLOPE TYPICAL UNIFORM BUILDING CODE USE AS CONSTRUCTED UTILITY EASEMENT UNDERGROUND ELECTRIC UNDERGROUND PHEAMSE
E E. ETY. EA. E.J. ELEC. ENG. EMTR. E.P. ECOUP. ER. ESMT. ESMT. E.T.R. EX. EXC. EXC. EXC. EXC.	EAST EASTELY EACH EXPANSION JOINT ELEVATION ELECTRICAL ENGINEER ENTRANCE ELICITRICAL ELOUP MENT ECOLOPINENT EACH EXPANSION EXPANSION EXTENSION EXPANSION EXPANSION EXPANSION EXPANSION EXPANSION EXPANSION EXPANSION EXPANSION	OPNG. OPPG. OPFG. OVT.  P. C. P.C. P.C. P.C. P.E. PERP. PH. P.I. P.I. PNI. PNI. P.O.B.	OPENING OPPOSITE OUTLET OUTLET OUNCE  POORT POINT OF CURVE PRECAST PORTLAND CEMENT CONCRETE POLYETHYLENE PEDESTRIA/PEDESTRIAN PERROVATED PERROVATED POINT OF INTERSECTION PROPERTY LINE PAINT POINT OF BEGINNING POINT OF TANGENT	UT UTV.  V V.R. V.C.P. V.C.P. V.C.P. V.P.C. V.P.C. V.P.C. V.P.T.  W W. W'LY. W/O W/O W/A	UNDERGROUND TELEPHONE UTILITY UNDERGROUND TELEVISION CABLE VARIES
F Fed F.D. F.D. F.I.C. F.I.C. F.O.C. F.O.LC. F.O.LV. F.T.I.C.	EXPANSION  FURNISH & INSTALL  FORCE MAIN  FLOOR DRAIN  FLOOR DRAIN  FLOOR DRAIN  FURNISHED AND INSTALLED BY CONTRACTOR  FURNISHED AND INSTALLED BY OWNER  FURNISHED AND INSTALLED BY TEMANT  FACE OF CONCRETE  FURNISHED BY OWNER, INSTALLED BY CONTRACTOR  FURNISHED BY OWNER, INSTALLED BY VENDOR  FURNISHED BY OWNER, INSTALLED BY CONTRACTOR  FURNISHED BY OWNER, INSTALLED BY CONTRACTOR  FURNISHED BY TEMANT, INSTALLED BY CONTRACTOR	P.O.T. P.P. P.R.C. P.REFAB. PROP. P.S.F. P.S.I. PT. PV. P.V.C. P.V.I. P.V.C. P.V.I. Q QTR.	POINT OF TANCENT POWER POLE PONT OF REVERSE CURVE PREFABRICATE PROPOSED POUNDS PER SQUARE FOOT POUNDS PER SQUARE INCH POINT PAVE POLYMYN, CHLORIDE POINT VERTICAL INTERSECTION PAVEMENT	WD. WD.W. WJ.W. W.R. W.S.O. WT. W.Y. W.W.F. W.W.F. Y 7D. Y.C.A.	WOOD WINDOW WATER MAIN WATER PROOF WASTE RECEPTACLE WATER SHUT OFF WEIGHT VALVE WATER YALVE WEIDED WIRE FABRIC WELDED WIRE FABRIC WELDED WIRE MESH CROSS SECTION YARD YAGGY COLBY ASSOCIATES

#### GENERAL NOTES

- ALL WORK SHALL CONFORM TO AND BE PERFORMED IN ACCORDANCE WITH ALL APPLICABLE CODES AND ORDINANCES.
- 2.) THE SPECIFICATIONS AS PREPARED BY IOWA DEPARTMENT OF AGRICULTURE AND YAGGY COLBY ASSOCIATES SHALL BE CONSIDERED A PART OF THESE DOCUMENTS AS IF BOUND HEREIN. NATURAL RESOURCES CONSERVATION SERVICE CONSTRUCTION SPECIFICATIONS SHALL APPLY.
- 3.) THE CONTRACTOR SHALL NOTIFY ALL APPROPRIATE ENGINEERING DEPARTMENTS AND UTILITY COMPANIES 72 HOURS PRIOR TO CONSTRUCTION. ALL NECESSARY PRECAUTIONS SHALL BE TAKEN TO AVOID DAMAGE TO ANY EXISTING UTILITY.
- 4.) THE LOCATION OF EXISTING UNDERGROUND UTILITIES AND ROCK ELEVATIONS ARE SHOWN IN AN APPROXIMATE WAY ONLY AND HAVE NOT BEEN INDEPENDENTLY VERIFIED BY THE OWNER OR ITS REPRESENTATIVE. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES AND ROCK ELEVATIONS BEFORE COMMENCING WORK, AND ACRES TO BE FULLY RESPONSIBLE FOR MY AND ALL DAMAGES WHICH MIGHT BE OCCASIONED BY THE CONTRACTOR'S FAILURE TO EXACITY LOCATE AND PRESERVE MY AND ALL UNDERGROUND UTILITIES AND ROCK ELEVATIONS. ROCK ELEVATIONS.
- 5.) THE CONTRACTOR SHALL VISIT THE SITE AND INSPECT THE PROJECT AREA AND THOROUGHLY FAMILIARIZE HINSELF WITH THE ACTUAL JOB CONDITIONS PRIOR TO BIODING AND THE START OF ANY WORK, FALURE TO VISIT THE SITE SHALL NOT RELIEVE THE CONTRACTOR FROM PERFORMING THE WORK IN ACCORDANCE WITH THESE DRAWINGS.
- 6.) THE CONTRACTOR SHALL VERFY AT THE SITE, ALL DIMENSIONS AND CONDITIONS SHOWN ON THE DRAWINGS, AND SHALL NOTIFY THE ENGINEER OF ANY DISCREPANCIES, OMISSIONS, AND/OR CONFLICTS PRIOR TO PROCEEDING WITH THE
- 7.) THE CONTRACTOR SHALL NOT SCALE DRAWINGS. DIMENSIONS SHALL COVERN, LARGE SCALE DRAWINGS SHALL GOVERN OVER SHALL SCALE DRAWINGS. NOTES AND DETAILS ON THE DRAWINGS SHALL APPLY TO ALL SHALLAR CONDITIONS WHETHER THEY ARE REPEATED OR NOT.

#### GRAPHIC SYMBOLS

GRAPHIC SYMBO	JL5	9/0	
	CENTER LINE	В/С	EXISTING CURB AND
	EASEMENT LINE	B/C	PROPOSED CURB & (
	RIGHT OF WAY LINE, PROPERTY LINE	B/C	PROPOSED 4" DRIVEO
	QUARTER SECTION LINE	=== <sup>B/C</sup> ===	FUTURE CURB & GUT
	SECTION LINE	TEXTING CONTRACTOR OF CONTRACT	REMOVE & RELAY EX
	SIXTEENTH SECTION LINE	Æ	
	BARBED WIRE FENCE	41	HANDICAPPED AREA
0	CHAIN-LINK FENCE		PEDESTRIAN CURB RA
1	WOODEN FENCE		DRAINAGE DIRECTION
	TREE UNE	Timost	ROCK PROFILE
0	1/2" REBARS	noome	NOON THOTIES
0	3/4" IRON PIPES	$\phi \rightarrow$	POWER POLE AND GL
•	FOUND MONUMENTS (PIPE, ROD, ETC)	·	
#		*	EXISTING LIGHT POLE
26 25 € 35 36 ≥	SECTION CORNER MARKER	*	PROPOSED LIGHT POL
100		<b>Ģ</b> €	TRAFFIC SIGNAL
RA		<b>@</b> #1	BORING LOCATION AND
364 Z	QUARTER SECTION MARKER	84.00	TOP OF CURB ELEVA
		a 00°	TOD OF DAVENEUT E
2* W/M	DOODOSED WATER HAIN MANUOLE TEE CATE VALVE LYDRANT	84:	TOP OF PAVEMENT E
	PROPOSED WATER MAIN, MANHOLE, TEE, CATE VALVE, HYDRANT, REDUCER, SERVICE LINE AND WATER SHUT OFF		SHRUB
	EXISTING WATER MAIN, MANHOLE, GATE VALVE AND HYDRANT		
¥	EXISTING WATER SHUT OFF		EXISTING DECIDUOUS
	PROPOSED SANITARY LINE, MANHOLE AND SERVICE LINE	ACC STATE OF THE PARTY OF THE P	
12" SAN. S.	EXISTING SANITARY MANHOLE AND LINE		
II.			EXISTING CONFEROUS
s.	PROPOSED STORM SEWER LINE, MANHOLE AND CATCH BASIN OR INTAKE	Millew.	
s.	EXISTING STORM SEWER MANHOLE, LINE AND CATCH BASIN OR INTAKE		PROPOSED OR NEW I
	EXISTING CATCH BASIN OR INTAKE	( <del>1</del>	TREE OR SHRUB SYM CALL-OUT RELATES TO SHOWN ON PLANTING
	EXISTING UNDERGROUND GAS LINE, VALVE AND METER		SHRUBS TO BE SHOW SIZE.
r⊠	EXISTING UNDERGROUND TELEPHONE MANHOLE, LINE AND PEDESTAL	(T-) Juntoly	PROPOSED OR NEW O
UE	EXISTING UNDERGROUND ELECTRIC MANHOLE, LINE AND TRANSFORMER	- January -	CALL-OUT RELATES TO SHOWN ON PLANTING SHRUBS TO BE SHOW
ATV ————————————————————————————————————	EXISTING UNDERGROUND TELEVISION LINE AND PEDESTAL	į.	SIZE.
F0	EXISTING FIBER OPTIC LINE		
	SAW CUT	TYPICAL HATCH PA	ATTERNS
uuumma	REMOVAL LIMITS	GROUTED RIP	////
		DECASO RAP	POOL E
		DEEP WATER AREA	LAYDOW
		ANCA CONTRACTOR	



EXISTING CURB AND GUTTER PROPOSED CURB & GUTTER

FUTURE CURB & GUTTER

PEDESTRIAN CURB RAMP

PROPOSED LIGHT POLE

BORING LOCATION AND NUMBER

TOP OF PAVEMENT ELEVATION

TOP OF CURB ELEVATION

EXISTING DECIDUOUS TREE

EXISTING CONFEROUS TREE

PROPOSED OR NEW DECIDUOUS TREE OR SHRUB SYMBOL. CALL-OUT RELATES TO NUMBERS SHOWN ON PLANTING SCHEDULE. SHRUBS TO BE SHOWN AT SMALLER

PROPOSED OR NEW CONIFEROUS TREE OR SHRUB SYMBOL. CALL-OUT RELATES TO NUMBERS SHOWN ON PLANTING SCHEDULE. SHRUBS TO BE SHOWN AT SMALLER

POOL EXCAVATION

LAYDOWN AREA

PERMANENT

POWER POLE AND GUY WIRE

REMOVE & RELAY EXISTING UTILITY

PROPOSED 4" DRIVEOVER CURB & GUTTER

PHONE: (641) 424-6344 215 N. ADAMS AVE.


# **PROJEC** E Mit981810C L COUNTY, IOWA REP OUNTY

SHEET

GENERAL INFORMATION

PAGE A	
PROJECT NUMBER	1211
COMPUTER FILE	12114C02.DV
DATE	05/15/201
DRAWN BY	AL
CHECKED BY	RC
REVISIONS	
#1 12-22	-14

H





PHONE: (641) 424-6344 215 N. ADAMS AVE. MASON CITY, IA 50401

a.

CREP WETLAN

D SIT

SITE Mit981810C

PLAN

SITE

MITCHELL COUNTY CREP

SHEET NUMB

C.03



PHONE: (641) 424-6344 215 N. ADAMS AVE. MASON CITY, IA 50401

OUNTY CREP WETLAND
SITE Mit981810C
STRUCTUR PLAN

PROJECT
NUMSER 12114
COMPUTER
FILE 12114DSUR.dwg

DATE 05/22/14

DRAWN BY ALH

CHEOXED BY RGL


REVISIONS
#1 12-22-14

SHEET NUMBER

C.04

of 7


### SHEET PILE STRUCTURE



SHEET PILE CROSS-SECTION N.T.S.

#### **DESIGN NOTES:**

- 1. DESIGN SHEET PILE AREA = 1077 SF
- 2. SHEET PILE: MINIMUM SECTION MODULUS 8.05 CU. IN. PER FT. OF WALL MINIMUM THICKNESS 0.25 IN. MINIMUM STEEL GRADE 36 KSI MEET ASTM A-328, A-572, OR A-690 MATERIAL SPECIFICATION MINIMUM MOMENT OF INERTIA OF 54.6 INCHES \*\*4 PER PILE
- 3. PILING TO BE INSTALLED STARTING FROM THE CENTER OF THE WIER SECTION AND PROGRESSING AWAY FROM CENTERLINE.



YAGGY

PHONE: (641) 424-6344 215 N. ADAMS AVE. MASON CITY, IA 50401


**PROJECT** COUNTY

SHEET PILE STRUCTURE

PROJECT NUMBER 12114C05.DWG 05/15/2014

#1 12-22-14

MITCHELL




PHONE: (641) 424-6344 215 N. ADAMS AVE. MASON CITY, IA 50401


SITE Mit981810C

DETAILS

COUNTY CREP WETLAND SITE MITCHELL

12114DSUR.dwg RGL #1 12-22-14





CONSTRUCTION TOP EL 1180.6

POOL NWL EL 1177.2

SPECIFICATIONS FOR REQUIREMENTS.

WATER CONTROL STRUCTURE

24" STUB


SPC - 2130

EL 1172.6


OUNTY

12114DETAIL.DWG 05/15/2014

#1 12-22-14



1" DIA. BOLT MINIMUM 3/8" **BOLT DETAIL** (N.T.S.)




#### NOTES:

- ALL BOLTS WILL BE 1" DIA. W/2 WASHERS. BOLT WILL EXTEND AT MINIMUM 3/8" BEYOND NUT.
- ALL HOLES WILL BE FIELD DRILLED 1/16" DIA. LARGER THAN THE BOLTS.
- 2 BOLTS WILL BE USED WHEN THE WALER IS PLACED NEXT TO THE SPLICE. 1 BOLT WILL BE USED WHEN WALER IS PLACED OPPOSITE THE SPLICE.

THE

WALER SHALL BE PLACED ON THE DOWNSTREAM SIDE OF




#### COVER/STOP LOG STORAGE STRUCTURE:

GEOTEXTILE

GROUTED RIPRAP DETAIL

- 1. BOTH PADLOCKS FOR WATER CONTROL STRUCTURE(WCS) AND STOPLOG STORAGE TUBE SHALL BE KEYED ALIKE. FOUR OF KEYS ARE TO BE SUPPLIED UPON PROJECT COMPLETION.
- 2. PROVIDE 24" GRATE AND COLLAR (AGRIDRAIN GR24P GRATE AND GRC24P COLLAR OR APPROVED EQUAL) FOR STOP LOG STORAGE.
- 3. STOP LOG STORAGE IS TO BE PLACED ADJACENT TO WCS AND AT AN ELEVATION EQUAL TO OR HIGHER THAN THE WCS.



PERFORATED RISER DETAIL

NOTES: 1. PERFORATED RISER TO BE LOCATED AT TOE OF EMBANKMENT.

2. PERFORATIONS SHALL BE 3-IN. DIAMETER,  $6"\pm C-C$  VERTICAL & 12"  $\pm$  HORIZONTALLY, WITH PERFORATIONS STAGGERED.

3. PERFORATIONS TO EXTEND FULL LENGTH OF RISER & ELBOW.

4. PERFORATED RISER, BASE AND BAR GUARD ARE INCIDENTAL COST SUBSIDIARY TO WATER CONTROL STRUCTURE.

5. NO GEOTEXTILE TO BE PLACED WITH RIPRAP.

EL. 1172.85

DATE \_\_\_\_05/15/14